

Super Deluxe Series

Solid Door Freezer

High Quality Stainless Steel Interior and Exterior Digitally Controlled Uniform Temperature

*** Digitally Controlled Temperature System**

Enables temperature control without opening the door.
Freshness of products lasts longer by keeping the correct temperature.

*** Efficient Refrigeration System**

Turbo Air's solid refrigerators and freezers are designed with over-sized evaporators and condensers for faster cooling and greater efficiency.

*** Bottom Mount Compressor**

All units feature a bottom-mount compressor for energy savings, high efficiency and easy service.
The bottom-mount compressor also allows the food to be placed in an ergonomically correct location.

*** Self-diagnostic System**

Shows the status of the freezer immediately.

*** Self-contained System**

No plumbing required. Simple installation.

*** Freezer holds -10°F for the best in food preservation-holds frozen food and ice cream**

*** Self-closing and Stay Open Door**

Door are equipped with self-closing and stay open feature.

*** Adjustable Stainless Steel Wire Shelves**

Durable and easy to adjust.

*** CEC. California Energy Commission Certificated**

*** MEA. City of New York Building Department Approved**



TSF-49SD



TSF-23SD



TSF-72SD



Model	Swing Door	CU./FT.	#of Shelves	HP	AMPS	Weight	L D H	List Price
TSF-23SD	1	23	3	1/3	7.8	285	27.0 x 30.8 x 77.9	4,891.00
TSF-35SD	2	35	6	3/4	10.3	360	39.5 x 30.8 x 77.9	Available Soon
TSF-49SD	2	49	6	3/4	10.3	462	54.4 x 30.8 x 77.9	6,996.00
TSF-72SD	3	72	9	1	10	670	81.9 x 30.8 x 77.9	9,810.00

* Height does not include 5" for caster height. **TSF-72SD** requires dual voltage 115/208-230V.



Super Deluxe Series

CABINET INTERIOR/EXTERIOR SPECIFICATIONS

ELECTRICAL DATA	TSF-23SD	TSF-49SD	TSF-72SD
Voltage	115/60-1	115/60-1	115/208~230
Feed Wires (With ground)	3	3	4
Wattage	550	900	1100
Amperes	7.8 A	10.3 A	10 A
SHIPPING DATA			
Length-Crated (in)	29.3	56.8	83.4
Depth-Crated (in)	33.7	33.7	33.7
Height-Crated (in)	84.3	84.3	84.3
Volume Crated (cu.ft)	48.1	87.3	135.7
Net Weight (lbs)	285	462	670
Weight After Packing (lbs)	330.7	529.1	758.4
DIMENSIONAL DATA			
# of Doors	1	2	3
Cubic Feet	23	49	72
Rack capacity	1	2	3
Length Overall (in)	27	54.4	81.9
Depth Overall (in)	30.8	30.8	30.8
Height Overall (in)(with caster)	82.9	82.9	82.9
Interior Dimension (LxDxH)	23x24.8x60.4	50.5x24.8x60.4	77.9x24.8x60.4
Shelf Size	21.6x23.3	24.4x23.3	24.4x23.3
# of Shelves	3	6	9

*** Bun Tray Rack Available**

All models are available for full door tray racks but lamp shield will have to be removed prior to being installed and re-assemble lamp and lamp-shield after installing racks.

*** Other Features**

- Solid and sturdy grill design.
- Minimum wattage heater in the cabinet frame to conserve energy and keep your cabinet water free.
- Incandescent interior lighting.
- Foamed with polyurethane, high-density cell insulation. (CFC free)
- Positive seal with closing doors.
- Automatic evaporator fan motor delay when the door is open.
- Left hinged TSF-23SD available.
- Door locks.
- 4"swivel casters. (standard)

*** 18 Month Labor and Parts Warranty for Super Deluxe Series**

*Design and specifications can be changed without prior notice for product improvement.

